



MODEL

Protect 900 (NV900)

Wall mountable, countertop with table stand or mounted on portable high tower, 2-NanoStrike coils, supplied with 1.6m power cord (minimum length).

CONSTRUCTION + COLOUR

Precision-cut fabricated metal casing in a white anti-bacterial powder coat finish.

DIMENSIONS

366 mm (h) x 365 mm (w) x 114 mm (d)
14.4" (h) x 14.4" (w) x 4.5" (d)

WEIGHT

4.7kg | 10.4 lbs

OPERATING CONDITIONS

10-35°C | 50-95°F, 10-75% Relative Humidity

SHIPPING/STORAGE CONDITIONS

5-50°C | 41-122°F, Maximum 95% Relative Humidity

ELECTRICAL RATING

Single Phase, 100-130 VAC | 220-240 VAC, 50-60 Hz
Fuse Rated at 250 VAC, 3 Amps, Listed

POWER CONSUMPTION RANGE*

100-130 VAC model:

Lowest speed: 11.4W – 14.4W
Highest speed: 14.1W – 18.3W

ELECTRICAL CONNECTION

Switched and fused with a grounded, moulded power cord.

FAN AIR FLOW VOLUME

Speed I = 220 m³/hr | 129 CFM
Speed II = 260 m³/hr | 153 CFM

NOISE LEVEL*

Speed I = 40 dB
Speed II = 45 dB

QUALITY STANDARDS

Manufactured under ISO 9001, ISO 14001
& OHSAS 45001

GLOBAL CERTIFICATIONS

IEC 60601-1
IEC 60601-1-2
IEC 60335-1
IEC 60335-2-65
Conforms to Low Voltage Directive (LVD) 2014/35/EU
CE
UL 867
cUL (CSA C22.2 NO. 187:20)
CARB
FCC
China Disinfection WS/T 648
KCC



* Power consumption depends on voltage and frequency of network in particular country
* Measured at the unit.